



Date of issue : 05/01/2005

Last. mod. date : 11/03/2009

**Product code****04353 RI-JET 100 MATT WHITE AVM semipermanent WK 140****Description**

Matt white soft vinyl, with good flexibility and conformability to curved surfaces.

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Removable adhesive with easy and clean removability from glass and from many substrates. Not recommended on paper, PVC, ABS, PS, air dried paints and varnishes.

For indoor and outdoor advertising and promotional applications.

**Technical data****FACE MATERIAL**

Type	Soft vinyl
Colour and Finish	White, matt
Weight	140g/m <sup>2</sup>
Thickness	100μ

**ADHESIVE**

Reference	RI - AVM
Type	Acrylic semi-permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C / +100°C
Shear	High
Tack	>2
Ultimate Adhesion	>2

**RELEASE BACKING**

Type	1 side clay coated
Colour and Finish	White
Weight	140g/m <sup>2</sup>
Thickness	135μ

**CHEMICAL RESISTANCE**

Detergent	No effect ( 24Hrs)
Gasoline	No effect (1Hrs)
SAE20 Motoroil	No effect (24Hrs)
10% HCl	No effect (10min)
10% NH4OH	No effect (10min)

**Storage**

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.