



Date of issue : 05/01/2005

Last. mod. date : 11/03/2009

Product code**02025 RI-JET 145 GLOSS WHITE AP permanent WK 140****Description**

Gloss white plasticised vinyl film, with good flexibility and conformability to curved surfaces.

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Permanent adhesive with very good adhesion on glass and on a wide variety of substrates, except for apolar (PE, PP).

For promotional graphics and point of sale advertising with medium outdoor durability.

Technical data**FACE MATERIAL**

Type	Plasticised vinyl film
Colour and Finish	White, Gloss
Weight	110g/m ²
Thickness	80μ

ADHESIVE

Reference	RI-AP
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Very High
Tack FTM9	6N/inch ²
FinAdh FTM2	9N/inch

RELEASE BACKING

Type	1 side clay coated
Colour and Finish	White
Weight	140g/m ²
Thickness	135μ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.